

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number  
**WO 2005/018979 A1**


- (51) International Patent Classification<sup>7</sup>: **B60L 11/18**
- (21) International Application Number:  
PCT/IB2004/002683
- (22) International Filing Date: 18 August 2004 (18.08.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
2003-300028 25 August 2003 (25.08.2003) JP
- (71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA [JP/JP]**; 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8561 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **ISHIKAWA, Tet-suhro [JP/JP]**; c/o Toyota Jidosha Kabushiki Kaisha,

1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP). **YOSHIDA, Hiroshi [JP/JP]**; c/o Toyota Communication Systems CO., LTD., NIK Nagoya Broadcasting Center Building, 1-13-3 Higashisakura, Higashi-ku, Nagoya, Aichi 461-0005 (JP). **SATO, Hitoshi [JP/JP]**; Apro Co., Ltd. of Crystal Nagoya Bill 5F, 1-11-5, Meieki-minami, Nakamura-ku, Nagoya-shi, Aichi 450-0003 (JP).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: FUEL CELL SYSTEM AND ELECTRIC VEHICLE INCLUDING THE FUEL CELL SYSTEM



(57) Abstract: In a fuel cell system in which load electric power is supplied from a fuel cell (20) and a secondary battery (30), intermittent operation is performed, that is, operation of the fuel cell (20) is stopped and the load electric power is supplied from the secondary battery (30) in a low load region. At this time, a threshold value for stopping and starting the operation of the fuel cell (20) is adjusted according to open circuit voltage (OCV) (step S180 to step S200). Thus, it is possible to prevent fuel from being unnecessarily consumed in order to maintain the open circuit voltage at a predetermined value when the operation of the fuel cell (20) is restarted after the open circuit voltage (OCV) has decreased in the fuel cell (20) that has stopped generating electric power.

ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CI, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NI, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*